

# HADRON R4320C FCC GRANT PART C

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification**

**Issued Under the Authority of the  
Federal Communications Commission**

**By:**

**EMCCert Dr. Rasek GmbH  
Stoernhofer Berg 15  
91364 Unterleinleiter,  
Germany**

**Date of Grant: 07/05/2019**

**Application Dated: 07/05/2019**

**CAEN RFID srl  
via Vetraia, 11 - 55049 Viareggio (LU) - ITALY  
Viareggio, 55049  
Italy**

**Attention: Adriano Bigongiari , CEO**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** UVECAENRFID027  
**Name of Grantee:** CAEN RFID srl  
**Equipment Class:** Part 15 Spread Spectrum Transmitter  
**Notes:** R4320C - Hadron - 4-port Embedded UHF RFID Reader  
**Modular Type:** Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
CC	15C	902.75 - 927.25	0.98		

Singular Modular Approval. Output power shown above is peak conducted. Co-location of this module with other transmitters that operate simultaneously are required to be evaluated using the FCC multi-transmitter procedures. The module antenna(s) must be installed to meet the RF exposure compliance separation distance of at least 25 cm and any additional testing and authorization process as required. The host integrator installing this module into their product must ensure that the final composite product complies with the FCC requirements by a technical assessment or evaluation to the FCC rules, including the transmitter operation and should refer to guidance in KDB 996369. This device is required to be professionally installed by a properly trained technician.

CC: This device is certified pursuant to two different Part 15 rules sections.